Lenovo TP TBT4 Dock G2 7000 - EU Andocken Thunderbolt 4 Schwarz



Marke : Lenovo

Artikel-Code: 40BG0135EU

Produktname : TP TBT4 Dock G2 7000 - EU

Lenovo TP TBT4 Dock G2 7000 - EU. Übertragungstechnik: Andocken, Hostschnittstelle: Thunderbolt 4, USB-Stromversorgung bis zu: 100 W. Ethernet LAN Datentransferraten: 2500 Mbit/s. Produktfarbe: Schwarz, Name der Farbe: Eclipse Black, Datenübertragungsrate: 40 Gbit/s. Breite: 220 mm, Tiefe: 80 mm, Höhe: 30 mm. Menge pro Packung: 1 Stück(e), Verpackungsbreite: 237,8 mm, Verpackungstiefe: 141 mm



Anschlüsse und Schnittstellen	
Übertragungstechnik *	Andocken
Hostschnittstelle *	Thunderbolt 4
USB 3.2 Gen 2 (3.1 Gen 2) Anzahl der Anschlüsse vom Typ A	4
USB 3.2 Gen 2 (3.1 Gen 2) Anzahl der Anschlüsse vom Typ C	2
USB Power Delivery	✔
USB-Stromversorgung Revision	3.1
USB-Stromversorgung bis zu	100 W
Anzahl HDMI-Anschlüsse *	1
HDMI-Version	2.1
Anzahl DisplayPort Anschlüsse	2
DisplayPorts-Version	1.4
Anzahl Thunderbolt 4-Ports	1
Mikrofon-Eingang *	✘

Netzwerk	
Ethernet/LAN *	✔
Anzahl Ethernet-LAN-Anschlüsse (RJ-45)	1
Ethernet LAN Datentransferraten	2500 Mbit/s

Leistungen	
Name der Farbe	Eclipse Black
Integrierter Kartenleser *	✘
Datenübertragungsrate	40 Gbit/s
HD-Typ	8K Ultra HD
Anzahl der Display unterstützt	4
Maximale Bildwiederholrate	60 Hz
Kabelsperre-Slot	✔

Leistungen	
Slot-Typ Kabelsperre	MicroSaver
Produktfarbe *	Schwarz
Ein-/Ausschalter	✔
Zertifizierung	FCC/ICES,CE,KCC,RCM,BSMI,NCC,VCCI,CB,cULus,EAC,TUV-Mark,LoA,Ukraine DoC,NOM,IFT,TELEC,UKCA,FAC DoC,VNTA,WPC ETA,SRRC,SDPPI,IMDA,SIRIM,NBTC, SUBTEL,KVALITET/RATEL,MCIT,ANRT,UCC,INACOM,CITRA,TRA,NTC,PSRC,NCA,ARTCI,INCM,Thunderbolt Cert.,EVO

Software	
Unterstützt Windows-Betriebssysteme	✔
Unterstützt Mac-Betriebssysteme	✔
Unterstützte Linux-Betriebssysteme	✔

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Relative Luftfeuchtigkeit in Betrieb	20 - 95%

Gewicht und Abmessungen	
Breite	220 mm
Tiefe	80 mm
Höhe	30 mm
Gewicht	547,5 g

Verpackungsdaten	
Menge pro Packung	1 Stück(e)
Verpackungsbreite	237,8 mm
Verpackungstiefe	141 mm
Verpackungshöhe	75,8 mm

Lieferumfang	
Mitgelieferte Kabel	AC
AC-Netzadapter	✔



0195892146766



195892146766

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 17-OCT-2026. Prints or copies of Information are only valid on the printed Publication date